

Vierkantstangen

Vierkantstangen, gezogen/gepresst nach EN 753/754/755 Square Bars, drawn/extruded, acc. to EN 753/754/755

Abm.	theor. Gew.	AlMgSi 0,5	AlMgSi 1	AlCuMgPb	AlZnMgCu 1,5
sizes	theor. weight				
mm	Kg/m	EN AW 6060	EN AW 6082	EN AW 2007	EN AW 7075
6	0,10	◆			
8	0,18	◆			
10	0,28	◆	◆	◆	
12	0,39	◆		◆	
14	0,53	◆			
15	0,61	◆	◆	◆	
16	0,70	◆			
20	1,10	◆	◆	◆	
25	1,70	◆	◆	◆	
30	2,50	◆	◆	◆	
32	2,85			◆	
35	3,30	◆	◆	◆	
40	4,40	◆	◆	◆	
45	5,47	◆	◆	◆	
50	6,75	◆	◆	◆	◆
55	8,17		◆	◆	
60	9,90	◆	◆	◆	◆
65	11,83		◆	◆	
70	13,72	◆	◆	◆	
75	16,03		◆	◆	
80	17,92	◆	◆	◆	◆
90	21,87	◆	◆	◆	
100	28,00	◆	◆	◆	◆
105	30,90		◆		
110	33,00		◆	◆	
115	36,00			◆	
120	39,00		◆	◆	◆
125	42,50		◆		
130	46,50		◆	◆	◆
140	54,90		◆	◆	◆
150	63,00		◆	◆	◆
160	71,80		◆	◆	◆
170	79,50		◆	◆	
180	90,70		◆	◆	◆
190	99,30		◆		
200	112,00		◆	◆	◆
220	135,50		◆	◆	
250	175,00		◆	◆	◆
300	252,00		◆		

- ◆ Lagervorrat
- Werksvorrat bzw. Neuanfertigung (auf Basis entsprechender Mindestmengen)
- ◆ Warehouse stock
- Mill stock or ex mill production (based on respective minimum quantities)